

SL2283 LED CLIPPER CEILING LIGHT 240MM 15W

Superlight LED Clipper light fittings are modern and stylish general purpose surface mounted LED ceiling fittings. They are an ideal LED alternative to oyster lights and other conventional ceiling light fittings.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	15W
LED Drive Current:	500mA
LED Classification:	SMD 3528
Beam Angle:	120°
Standard Finish:	Matt White
Dimmable:	Yes
Dimensions Depth:	39mm
Dimensions Diameter:	180mm
IP Rating:	IP44
Recommended Operating Temp:	-5 ~ +55°C



PHOTOMETRIC INFORMATION

SL2283-15	CCT: 6500K CRI: >80
SL2283-17	CCT: 4200K CRI: >85
SL2283-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General area lighting in commercial and residential applications, Retrofit replacement for existing oyster style light fittings.

CONTROL & DIMMING COMPATIBILITY

Superlight LED Clipper fittings are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

ORDERING INFORMATION

SL2283-15	Superlight LED Clipper 15W 240mm 6500K COOL WHITE
SL2283-17	Superlight LED Clipper 15W 240mm 4200K NEUTRAL WHITE
SL2283-21	Superlight LED Clipper 15W 240mm 3200K WARM WHITE

Product specifications & details are subject to change without notice.

CUSTOMISATION OPTIONS

Fitting colour can be refinished

Remote mounted DALI dimmable driver available by request

Superlight can also manufacture square body by special request

Customisation options are subject to availability and minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.