

## SL2290 13W COMPACT LED DOWNLIGHT FITTING

Superlight SL2290 Compact LED Downlight fittings are revolutionary in their fixture design and performance. With an extremely compact slimline design, they are ideal for projects with very limited ceiling depth. The fittings are supplied complete with Superlight dimmable LED driver.

### SPECIFICATIONS

Driver Input Voltage:	240VAC
Max Power Consumption:	13 Watts
LED Quantity:	Single 13W MV-X LED
LED Classification:	High Power MV-X 13W (700mA)
Drive Current:	Constant Current
Standard Beam Angle:	60° Wide Beam
Colour Temp (CW/WW)	6500K/3200K
Physical Dimensions:	Trim:105mm Cutout:90mm
Minimum Ceiling Depth Required:	35mm Depth - Compact
Dimmable:	Yes (dimmable driver included)
Operating Temperature:	-5 ~ +55°C

### PHOTOMETRIC INFORMATION

SL2290-15	CCT: 6500K CRI: >80
SL2290-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

General lighting in residential projects with very low ceiling depth, Retrofitting of existing halogen style LED downlights.

### CONTROL & DIMMING COMPATIBILITY

Superlight SL2290 Compact LED Downlights are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

### ORDERING INFORMATION

SL2290-15	13W Compact LED Downlight 6500K COOL WHITE
SL2290-21	13W Compact LED Downlight 3200K WARM WHITE

### CUSTOMISATION OPTIONS

Trim colour can be refinished  
Dali dimmable driver available by request  
CCT 4200K available by request  
Customisation options are subject to minimum order quantities

