

SL2401 SURFACE MOUNTED LED CLIPPER IP44

Superlight IP44 Polycarbonate LED Clipper light fittings are multipurpose fittings with a vandal resistant polycarbonate body and integral on-board 10W LED. The fittings are rated to IP44 and are ideal for all indoor or outdoor general purpose lighting applications.

SPECIFICATIONS

Input Voltage:	100-250VAC
Max Power Consumption:	10W
LED Drive Current:	400mA
LED Classification:	SMD 3528
Beam Angle:	160°
Standard Finish:	Semi-Transparent Polycarbonate
Recommended Operating Temp:	-5 ~ +55 °C
Dimmable:	No
Dimensions Depth:	72mm
Dimensions Diameter:	260mm
IP Protection Rating:	IP44



PHOTOMETRIC INFORMATION

SL2401-15	CCT: 6000K CRI: >75
SL2401-17	CCT: 4200K CRI: >78
SL2401-21	CCT: 3200K CRI: >78

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General area lighting in commercial and residential applications, Retrofit replacement for existing oyster style light fittings, Utility lighting and public spaces

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2401-15	LED Polycarbonate Clipper 10W 6500K COOL WHITE
SL2401-17	LED Polycarbonate Clipper 10W 4200K NEUTRAL WHITE
SL2401-21	LED Polycarbonate Clipper 10W 3200K WARM WHITE

Product specifications & details are subject to change without notice.

CUSTOMISATION OPTIONS

Semi-transparent polycarbonate can be frosted by special request
Customisation options are subject to availability and minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.