

## SUPERLIGHT BUTTON LED OYSTER SERIES

The Superlight Button is a surface mounted ceiling light fitting with polycarbonate diffuser and integral LED driver. The Button series is an ideal alternative to traditional oyster style light fittings and is suited to residential projects and developments. Superlight Button series is available in two main sizes.

### SPECIFICATIONS

Model:	Button 350	Button 275
Part Number:	SL2435	SL2434
Input Voltage:	240VAC	240VAC
Power Consumption:	25W	15W
Diameter:	350mm	275mm
Overall Height:	110mm	100mm
Fixture Material:	Polycarbonate	Polycarbonate
LED Classification:	SSC SMD LED	SSC SMD LED
LED Drive Current:	600mA	600mA
Typical Light Source Efficacy:	90lm/W	90lm/W
Light Source CRI:	>85	>85
Beam Angle:	120° Diffused	120° Diffused
Recommended Ambient Tem:	-10 ~ +40°C	-10 ~ +40°C
IP Protection Rating:	IP20	IP20

### PHOTOMETRIC INFORMATION

SL2434/35-15	CCT: 5700K CRI: >85
SL2434/35-17	CCT: 4000K CRI: >85
SL2434/35-21	CCT: 3000K CRI: >85

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Multi-level residential projects, apartments, common areas, stairwells foyers, general purpose lighting, storage and utility spaces.

### CONTROL & DIMMING COMPATIBILITY

Superlight Disc LED oysters are supplied with phase control dimmable LED drivers

Optional DALI dimmable LED driver is available by special request

Optional 1-10V dimmable LED driver is available by special request

### ORDERING INFORMATION

SL2434-21	Button 275mm LED Oyster Dimmable LED Driver 15W 3000K
SL2434-17	Button 275mm LED Oyster Dimmable LED Driver 15W 4000K
SL2434-15	Button 275mm LED Oyster Dimmable LED Driver 15W 5700K
SL2435-21	Button 350mm LED Oyster Dimmable LED Driver 25W 3000K
SL2435-17	Button 350mm LED Oyster Dimmable LED Driver 25W 4000K
SL2435-15	Button 350mm LED Oyster Dimmable LED Driver 25W 5700K

### CUSTOMISATION OPTIONS

Superlight can supply versions with integrated movement sensors by request

Optional 2HR emergency lighting configuration available by special request.

\*\*Custom options may be subject to minimum order quantities

