

## SL2441 DICE-R RECESSED LED DOWNLIGHT FITTING

Superlight Dice-R is a series of recessed LED downlights for architectural use. The fittings incorporate a linear series of high quality LED modules fitted into an extruded aluminium body. The fittings are ideal for a range of applications including display case lighting, ceiling downlighting, and task lighting.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	3W
Trim Dimensions:	54x54mm
Ceiling Cutout:	32x32mm
LED Classification:	CREE High Power LED
LED Quantity:	1
Colour/Finishes:	Charcoal Black or White
Fixture Material:	Aluminium
Typical Light Source Efficacy:	100lm/W
Beam Angle Options:	25°/60°/80°
Optional Accessories:	Customised Track System
Recommended Ambient Temp:	-10 ~ +50°
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

SL2441-15	CCT: 6000K CRI: >95
SL2441-17	CCT: 4000K CRI: >95
SL2441-21	CCT: 3000K CRI: >95

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Hotels and hospitality projects, showrooms and displays, residential lighting, display cases, joiner, ceiling downlighting, commercial fitouts, accent lighting, task lighting.

### CONTROL & DIMMING COMPATIBILITY

Dice-R LED downlights are supplied with phase control dimmable LED drivers

Optional DALI dimmable LED driver is available by special request

Optional 1-10V dimmable LED driver is available by special request

### ORDERING INFORMATION

SL2441**25-21	Dice-R LED Downlight White 25deg 3W 3000K
SL2441**25-17	Dice-R LED Downlight White 25deg 3W 4000K
SL2441**25-15	Dice-R LED Downlight White 25deg 3W 6000K
SL2441**60-21	Dice-R LED Downlight White 60deg 3W 3000K
SL2441**60-17	Dice-R LED Downlight White 60deg 3W 4000K
SL2441**60-15	Dice-R LED Downlight White 60deg 3W 6000K
SL2441**80-21	Dice-R LED Downlight White 80deg 3W 3000K
SL2441**80-17	Dice-R LED Downlight White 80deg 3W 4000K
SL2441**80-15	Dice-R LED Downlight White 80deg 3W 6000K

\*\* Specify trim colour White or Charcoal Black

### CUSTOMISATION OPTIONS

Optional linear continuous track mounting system is available by special request

Trim colour can be refinished by special request

\*\*Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

