

## SL2756 12W ECO-75 SERIES RECESSED LED DOWNLIGHT

Superlight ECO-75 is a high quality LED downlight series with an extremely fine trim for superior ceiling fit. The LED light source is supported with premium optical lens and internal reflector to deliver optimum photometric performance whilst minimising glare and light spill. ECO-75 is available in three main size variants.

### SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	12W
Trim Dimensions:	98mm
Ceiling Cutout:	90mm
Fitting Depth:	94mm
LED Classification:	Sharp COB LED
LED Drive Current:	260mA
Materials:	Aluminium Alloy, Powdercoated
Typical Light Source Efficacy:	100lm/W
Beam Angle Options:	55°
LED Driver Power Factor:	>0.9
Recommended Ambient Temp:	-10 ~ +40°C
IP Protection Rating:	IP54



### PHOTOMETRIC INFORMATION

SL2756-15	CCT: 6000K CRI: >90
SL2756-17	CCT: 4000K CRI: >90
SL2756-21	CCT: 3200K CRI: >90

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

High-end residential and commercial interiors, architectural projects. office interiors, retail and shopfitting projects. museums, galleries, showrooms.

### CONTROL & DIMMING COMPATIBILITY

SL2756 LED downlights are supplied with phase control dimmable LED drivers

Optional DALI dimmable LED driver is available by special request

Optional 1-10V dimmable LED driver is available by special request

### ORDERING INFORMATION

SL2756-21	Superlight ECO75-12W Recessed LED Downlight 3200K
SL2756-17	Superlight ECO75-12W Recessed LED Downlight 4000K
SL2756-15	Superlight ECO75-12W Recessed LED Downlight 6000K

### CUSTOMISATION OPTIONS

Fixture trim can be refinished by special request

Black trim colour available by request

\*\*Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.