

SUPERLIGHT SL2856 SATURN 190 LED DOWNLIGHT SERIES

Superlight Saturn 190 is a LED downlight fitting for general purpose down lighting applications. The product is ideally suited to commercial projects or residential spaces such as common areas. The fittings incorporate high efficiency polished specular reflector to deliver optimum illumination performance.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	18W / 25W / 35W
Trim Dimensions:	190mm
Ceiling Cutout:	160-170mm
Fitting Depth:	75mm
LED Classification:	Sharp COB
LED Quantity:	1
Reflector Design	Semi Specular Polished Reflector
Fixture Material:	Aluminium + Alloy Heatsink
Typical Light Source Efficacy:	110lm/W
Beam Angle:	60°
Recommended Ambient Temp:	-10 ~ +40°C
IP Protection Rating:	IP44



PHOTOMETRIC INFORMATION

SL2856-15	CCT: 6000K CRI: >90
SL2856-17	CCT: 4000K CRI: >90
SL2856-21	CCT: 3000K CRI: >90
SL2856-27	CCT: 2700K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial projects, retail showrooms, offices, foyers, common areas, residential developments, airports galleries, museums, food preparation areas, clubs and restaurants, hotels.

CONTROL & DIMMING COMPATIBILITY

Saturn LED downlights are supplied with phase control dimmable LED drivers

Optional DALI dimmable LED driver is available by special request

Optional 1-10V dimmable LED driver is available by special request

ORDERING INFORMATION

SL2856-27	Saturn LED Downlight 190mm Trim Dimmable Driver 2700K
SL2856-21	Saturn LED Downlight 190mm Trim Dimmable Driver 3000K
SL2856-17	Saturn LED Downlight 190mm Trim Dimmable Driver 4000K
SL2856-15	Saturn LED Downlight 190mm Trim Dimmable Driver 5000K

**Specify Wattage Configuration 18W / 25W / 35W

CUSTOMISATION OPTIONS

Fixture trim can be refinished by special request

Optional DALI dimmable driver by special request

**Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.