

SL2863 HALF ROUND ARCHITECTURAL LED WALL LIGHT FIXTURE

Superlight SL2863 is a modern architectural wall light fixture suitable for high end projects. SL2863 is Ip65 rated suitable for interior and exterior applications. It has integral LED driver and high efficiency LED components. The high grade body is finished in corrosion resistant powdercoat finish and is available in white or black.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	6W
Depth From Wall:	50mm
Dimensions:	126x100mm
LED Classification:	Cree CXA
Colour/Finish:	Powdercoated
Fixture Material:	Aluminium
Typical Light Source Efficacy:	90lm/W
Beam Angle Options:	45°
Mounting Orientation:	Wall Mounted
Recommended Ambient Temp:	-10 ~ +40°C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

SL2863-15	CCT: 6000K CRI: >90
SL2863-17	CCT: 4000K CRI: >90
SL2863-21	CCT: 3000K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include architectural projects, exterior lighting, columns and pillars, interior projects, hotels and accommodation, public spaces, hospitality projects, restaurants, retail and showrooms, galleries.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

INSTALLATION METHOD

SL2863 is a wall mounted LED fixture suitable for interior or exterior use. The product features internal adjustable light guide blades to control the illumination effect. The fitting has integral constant current LED driver.

ORDERING INFORMATION

SL2863BK-21	Half-Round LED Wall Light BLACK 3000K
SL2863BK-17	Half-Round LED Wall Light BLACK 4000K
SL2863BK-15	Half-Round LED Wall Light BLACK 6000K
SL2863WH-21	Half-Round LED Wall Light WHITE 3000K
SL2863WH-17	Half-Round LED Wall Light WHITE 4000K
SL2863WH-15	Half-Round LED Wall Light WHITE 6000K

CUSTOMISATION OPTIONS

LED CCT or special LED colour available by special request

Fixture colour can be refinished by special request

**Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

