

## SL2949 REVO 16W ADJUST LED DOWNLIGHT

Superlight Revo 16W LED downlights incorporate the latest Single MX-V LED technology to provide exceptional light output and performance whilst consuming minimal energy consumption. The Revo LED Downlights can be used in any high-end residential or commercial project.

Revo LED downlights come complete w/ a Superlight dimmable driver & have wide 60° beam angle making them ideal for all general ceiling downlighting applications.

### SPECIFICATIONS

Input Voltage:	240VAC
Max Power Consumption:	16 Watts
LED Quantity:	1 x 16W MV-X LED
LED Classification:	High Power Sharp MV-X 16W
Drive Current Type:	700mA
Standard Beam Angle:	60° Wide Beam
Colour Temp (CW/WW)	6000K/3000K
Physical Dimensions:	Trim:105mm Cutout:90mm
Minimum Ceiling Depth Required:	95mm
Dimmable:	Yes (dimmable driver included)
Recommended Ambient Temp:	-5 ~ +55°C

### PHOTOMETRIC INFORMATION

SL2949-15	CCT: 6500K CRI: >80
SL2949-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

General lighting in residential projects with med to high ceiling heights. Commercial & retail fit-outs. Retrofitting of existing halogen style LED downlights

### CONTROL & DIMMING COMPATIBILITY

Revo-16 LED Downlights are supplied with Superlight dimmable LED drivers which are compatible with most Australian universal style dimmers.

### ORDERING INFORMATION

SL2949-15	Revo 16W Adjust LED Downlight 6500K COOL WHITE
SL2949-21	Revo 16W Adjust LED Downlight 3200K WARM WHITE

### CUSTOMISATION OPTIONS

Trim colour can be refinished  
Dali dimmable driver available by request  
CCT 4200K available by request  
Customisation options are subject to minimum order quantities

