

## SL2956 ECO18 RECESSED LED DOWNLIGHT

ECO18 Recessed LED downlight incorporates a high power Sharp MV-X LED in a stylish & contemporary semi-trimless fixture design. ECO18 LED downlights have a wide 60° beam which is optimised for general area downlighting applications.

Each ECO18 fitting comes complete with a Superlight dimmable driver which allows smooth dimming via standard leading-edge, trailing edge and universal style dimmers.

### SPECIFICATIONS

Input Voltage:	240VAC
Max Power Consumption:	15 Watts
LED Quantity:	1
LED Classification:	Sharp High Power
Drive Current Type:	320mA
Standard Beam Angle:	60° Beam
Physical Dimensions:	Trim: 125mm Ceiling Cutout:115mm
Minimum Ceiling Depth Required:	120mm
Dimmable:	Yes (Dimmable Driver Included)
IP Protection Rating:	IP44
Recommended Ambient Temp:	-5 ~ +55°C



### PHOTOMETRIC INFORMATION

SL2956-21 Warm White	CCT 3000K CRI >90
SL2956-17 Neutral White	CCT 4200K CRI >85
SL2956-15 Cool White	CCT 6000K CRI >85

### TYPICAL APPLICATIONS

Typical applications include high-end commercial fitouts. Retail environments, shopping centres, offices, high-end residential projects.

### CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

### ORDERING INFORMATION

SL2956-15	ECO18 LED Downlight 15W Cool White 6000K
SL2956-17	ECO18 LED Downlight 15W Neutral White 4200K
SL2956-21	ECO18 LED Downlight 15W Warm White 3000K

### CUSTOMISATION OPTIONS

Fixture colour can be refinished  
Can be fitted with optional 15W, 18W or 26W Sharp LED  
Dali Dimmable Driver available by request  
Customisation options are subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.