

SUPERLIGHT REVO-XR26 RECESSED LED DOWNLIGHT

Superlight Revo-XR26 is a quality LED downlight fitting suitable for high-end interior projects. The fitting features an internal polished specular reflector with integrated LED light source which delivers superior optical performance and aesthetic.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	26W
Trim Diameter:	175mm
Ceiling Cutout:	165mm
Fixture Depth:	130mm
LED Classification:	Single 26W Sharp MX-V LED
Reflector Configuration:	Semi-Specular Polished Reflector
Typical Light Source Efficacy:	110lm/W
LED Light Source CRI:	>90
Beam Angle:	60°
Power Factor:	>0.9
Recommended Ambient Temp:	-5 ~ +55°C
IP Protection Rating:	IP44



PHOTOMETRIC INFORMATION

SL2968-15	CCT: 6000K CRI: >90
SL2986-17	CCT: 4000K CRI: >90
SL2986-21	CCT: 3200K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

High-end residential decors, commercial projects, retail showrooms, hotels and hospitality projects, common areas, office fitouts, malls and galleries, airports, education and government projects.

CONTROL & DIMMING COMPATIBILITY

Revo-XR26 LED downlights are supplied with phase control dimmable LED drivers

Optional DALI dimmable LED driver is available by special request

Optional 1-10V dimmable LED driver is available by special request

ORDERING INFORMATION

SL2986-15	Superlight Revo-XR26 LED Downlight Dimmable Driver 3200K
SL2986-17	Superlight Revo-XR26 LED Downlight Dimmable Driver 4000K
SL2986-21	Superlight Revo-XR26 LED Downlight Dimmable Driver 6000K

CUSTOMISATION OPTIONS

Trim fixture can be refinished by special request

Optional DALI dimmable version by special request

**Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.