

SUPERLIGHT SL3054 RECESSED MINI LIGHT IP67

Superlight SL3054 is a very low profile LED fitting suitable for recess mounting in floors, decking and pavers. The fitting is fabricated from stainless steel and features high brightness 3350 SMD LED technology which delivers strong light output whilst minimising energy consumption.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	0.7W
Facia Configuration:	
Fitting Trim Dimensions:	58x58mm
Cutout Dimensions:	51x51mm
Overall Depth:	9mm
LED Classification:	SMD3350
LED Quantity:	8
Colour/Finish:	Brushed Steel
Typical Light Source Efficacy:	80lm/W
Diffuser Material:	High Intensity Glass
Beam Angle:	120°
Mechanical Rating:	Walk-Over Rating
Recommended Ambient Temp:	-10 ~ +40°C
Compatible Control Options:	DALI, DMX, 1-10V
IP Protection Rating:	IP67

PHOTOMETRIC INFORMATION

SL3054-15	CCT: 6000K CRI: >80
SL3054-17	CCT: 4000K CRI: >80
SL3054-21	CCT: 3000K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Landscape lighting, driveways and pathway lighting, display cabinets, furniture lighting, marine & automotive applications, floor lighting, deck lighting.

CONTROL & DIMMING COMPATIBILITY

SL3054 is dimmable using any superlight constant voltage dimming controller. Specific dimming options include PWM, DALI, DMX, 1-10V
RGB option is colour-controllable via Superlight RGB LED Controller

ORDERING INFORMATION

SL3054-21	Superlight Stainless Steel Recessed LED 58x58mm 3000K
SL3054-17	Superlight Stainless Steel Recessed LED 58x58mm 4000K
SL3054-15	Superlight Stainless Steel Recessed LED 58x58mm 6000K

CUSTOMISATION OPTIONS

Fixture colour can be refinished by special request
Superlight can design and supply dimming control or RGB control systems
Custom options may be subject to minimum order quantities

