

## SUPERLIGHT SL3059 RECESSED MINI LIGHT IP67

Superlight SL3059 is a low profile LED fitting suitable for recess mounting in floors, decking and pavers. The fitting is fabricated from stainless steel and features high brightness 3350 SMD LED technology which delivers strong light output whilst minimising energy consumption.

### SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	0.7W
Fitting Trim Dimensions:	59x59mm
Cutout Dimensions:	55x55mm
Overall Depth:	28mm
LED Classification:	SMD3350
LED Quantity:	8
Colour/Finish:	Brushed Steel
Typical Light Source Efficacy:	80lm/W
Diffuser Material:	Opal Polycarbonate
Mechanical Rating:	Drive-Over Rated
Beam Angle:	120°
Included Accessory:	Stainless Steel Mounting Niche
Recommended Ambient Temp:	-10 ~ +40°C
Range of Colour Output:	16.7million + (RGB Version)
Compatible Control Options:	DALI, DMX, 1-10V
IP Protection Rating:	IP67

### PHOTOMETRIC INFORMATION

SL3059-15	CCT: 6000K CRI: >80
SL3059-17	CCT: 4000K CRI: >80
SL3059-21	CCT: 3000K CRI: >80
SL3059-35	RGB

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Landscape lighting, driveways and pathway lighting, display cabinets, furniture lighting, marine & automotive applications, floor lighting, deck lighting.

### CONTROL & DIMMING COMPATIBILITY

SL3059 is dimmable using any superlight constant voltage dimming controller. Specific dimming options include PWM, DALI, DMX, 1-10V  
RGB option is colour-controllable via Superlight RGB LED Controller

### ORDERING INFORMATION

SL3059-21	Superlight Stainless Steel Recessed LED 59x59mm 3000K
SL3059-17	Superlight Stainless Steel Recessed LED 59x59mm 4000K
SL3059-15	Superlight Stainless Steel Recessed LED 59x59mm 6000K
SL3059-35	Superlight Stainless Steel Recessed LED 59x59mm RGB

### CUSTOMISATION OPTIONS

Fixture colour can be refinished by special request  
Superlight can design and supply dimming control or RGB control systems  
Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

