

SL3422 SQUARE LED DOWNLIGHTER 25W

Superlight SL3422 Grid LED Downlight fittings are suitable for decorative and architectural downlighting applications. The fittings feature a modern, low glare 25W LED arrangement and low profile fitting design.

SPECIFICATIONS

Driver Input Voltage:	110 - 140 VAC
Max Power Consumption:	25W
LED Quantity:	25 x 1W
LED Classification:	High Power XR
Viewing Angle:	120°
Trim Dimensions:	198 x 198mm
Ceiling Cutout:	180 x 180mm
Minimum Ceiling Depth Required:	65mm
Dimmable:	No
IP Rating:	IP20
Recommended Operating Temp:	-5°C ~ +55°C



PHOTOMETRIC INFORMATION

SL3422-15	CCT: 6500K CRI: >80
SL3422-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial and residential projects, Food handling areas,
Common area downlighting

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL3422-15	25W Grid LED Downlight Fitting 6500K COOL WHITE
SL3422-21	25W Grid LED Downlight Fitting 3200K WARM WHITE

Product specifications & details are subject to change without notice.

CUSTOMISATION OPTIONS

Trim colour can be refinished by request
Dali dimmable driver available by request
Customisation options are subject to availability and minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.