

SUPERLIGHT SL3435 D36 RECESSED LED SHOPLIGHTER

Superlight SL3435-D36 is a high quality commercial light fixture, specifically designed for commercial spaces and retail environments. The D36 fitting features fitted LED optics for delivering focused illumination, making the product ideal for task lighting of products and displays within commercial retail spaces.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	35W / 40W
Trim Dimensions:	235x145mm
Ceiling Cutout:	220x130mm
LED Classification:	Superlight VT Linear COB
LED Quantity:	Single LED Array
Typical Light Source Efficacy:	95lm/W
LED Light Source CRI	>85
Beam Angle:	36°
Fixture Material:	Powdercoat Aluminium
Recommended Ambient Temp:	-15 ~ +55°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL3435D36-15	CCT: 5700K CRI: >85
SL3435D36-17	CCT: 4000K CRI: >85
SL3435D36-21	CCT: 3000K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Focussed task lighting, retail and shopfitting projects, commercial projects, common areas, showrooms, airports, museums, schools and education projects, government sector projects, wall washing, task lighting, showcases and galleries.

CONTROL & DIMMING COMPATIBILITY

SL3435 series is supplied with non-dimmable LED drivers by default. Optional DALI or 1-10V dimmable version is available by special request.

ORDERING INFORMATION

SL3435D36-21D36	LED Shoplighter LED Driver 36deg 35W 3000K
SL3435D36-17D36	LED Shoplighter LED Driver 36deg 35W 4000K
SL3435D36-15D36	LED Shoplighter LED Driver 36deg 35W 5700K
SL3440D36-21D36	LED Shoplighter LED Driver 36deg 40W 3000K
SL3440D36-17D36	LED Shoplighter LED Driver 36deg 40W 4000K
SL3440D36-15D36	LED Shoplighter LED Driver 36deg 40W 5700K

CUSTOMISATION OPTIONS

40W LED option available by request

Fixture colour can be refinished

DALI dimmable version by special request

**Custom options may be subject to minimum order quantities

