

SL4411 XDL SERIES SURFACE MOUNT LED DOWNLIGHT

Superlight XDL series is a high quality surface mounted LED downlight fixture for architectural lighting applications. The fitting features an integral LED driver and new generation Sharp LED. The high performance low-glare reflector delivers superior illumination whilst minimising glare and unnecessary light spill.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	20W / 25W / 30W
Dimensions:	138(h)x168mm(d)
LED Classification:	Sharp XDL LED
LED Quantity:	1
Standard Colour/Finishes:	White
Fixture Material:	Cast Alloy & Powdercoated
Typical Light Source Efficacy:	100lm/W
Beam Angle Options:	55°
Recommended Ambient Temp:	-10 ~ +40°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL4411-15	XDL CCT: 5000K CRI: >90
SL4411-17	XDL CCT: 4000K CRI: >90
SL4411-21	XDL CCT: 3000K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Concrete slab ceilings, residential and commercial projects, offices, hospitality, hotels, cafes, galleries and museums, showrooms, retail environments, shopping centres.

CONTROL & DIMMING COMPATIBILITY

XDL series is supplied with integral dimmable driver - phase control dimmable
Fitting is dimmable using most standard style phase control dimmers

ORDERING INFORMATION

SL4411-15	Surface Mount LED Downlight Dimmable 5000K
SL4411-17	Surface Mount LED Downlight Dimmable 4000K
SL4411-21	Surface Mount LED Downlight Dimmable 3000K

** Specify LED output option: 20W / 25W / 30W

CUSTOMISATION OPTIONS

Fixture colour can be refinished silver/black
Custom colours available by special request
Remote mounted DALI driver by special request

**Custom options may be subject to minimum order quantities

