

SL8322 FLOORMOUNT LED LIGHTING PROFILE

Superlight SL8322 LED mounting profile is designed for floor-mounting of Superlight linear LED strips. The profile is used in theatres but can be used for any application where a surface mounted option is required. The profile can also be wall or ceiling mounted if necessary.

SPECIFICATIONS

Standard Profile Length:	2mtr
Custom Lengths Available:	Yes
Profile Dimensions:	52mm x 9.2mm
Standard Finish:	Anodised Silver
Custom Colours/Finishes	Dulux Powdercoat
Compatible LED Product:	Superlight LED Superstrip
Lens:	Opal PMMA Lens Diffuser



PHOTOMETRIC INFORMATION

Photometric performance is dependant on LED configuration.

TYPICAL APPLICATIONS

Commercial floor lighting, decorative lighting, clubs & venues, nightclubs, restaurants & cafes, public spaces, decorative lighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL8322-00	Aluminium Extruded Floor-Mounted LED Mounting Profile
SL8322-12	Polycarbonate LENS Diffuser for SL8322 Profile

CUSTOMISATION OPTIONS

- Supplied in custom lengths by request
- Various LED configuration options
- Mounting profile can be powdercoated by request
- RGB control or dimmable single colour control options
- Interior & Exterior IP rated options

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.