

SL8606 DUAL LED TURBOSTRIP 39.8W

DUAL LED Turbostrip is a customised linear LED product with exceptional light output. It is designed for linear LED lighting applications requiring extremely high light output and performance. DUAL LED Turbostrip incorporates the same V-LED technology as the Generation-3 LED Turbostrip. Typical applications include high intensity backlighting, and other demanding indirect lighting projects. When used in conjunction with the SL8550 LED mounting profile, DUAL LED Turbostrip is suitable for many task lighting projects and general area lighting applications.

SPECIFICATIONS

Input Voltage:	24VDC
Max Power Consumption:	39.8W per mtr
LED Quantity:	240 per mtr
LED Classification:	Generation-3 SSC SMD V-LED
Viewing Angle:	20°
Standard Length:	Superlight Can Supply Any Length
Max Single Length:	5mtrs (recommended)
Heatsink Required:	Yes (Use SL8550 Mounting Profile)
Strip Dimensions:	18 x 3.5mm
Colour Temp(cw/ww):	6500K/3200K
Recommended Ambient Temp:	-5 ~ +55 °C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL8606-15	CCT: 6500K CRI: >80
SL8606-17	CCT: 4200K CRI: >85
SL8606-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include high intensity backlighting, and other demanding indirect lighting projects. When used in conjunction with the SL8550 LED mounting profile, DUAL LED Turbostrip is suitable for many task lighting projects and general area lighting applications.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL8606-15	DUAL LED Turbostrip 39.6W 24VDC 6500K Cool White
SL8606-17	DUAL LED Turbostrip 39.6W 24VDC 4200K Neutral White
SL8606-21	DUAL LED Turbostrip 39.6W 24VDC 3200K Warm White

CUSTOMISATION OPTIONS

Superlight can manufacture any required lengths
Compatible with Superlight DMX521, DALI and Analogue 1-10V Controllers
Can be supplied complete with mounting profile



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.