

SL9003 30W MX LED AREA FLOODLIGHT

Superlight 9000 series LED floodlights incorporate the latest MX LED technology to deliver incredible light output and performance. The fittings operate on standard 100-240VAC mains voltage and require zero lamp maintenance.

SPECIFICATIONS

Input Voltage:	100-240VAC
Dimensions (W x H x D):	225 x 185 x 126mm
Max Power Consumption (Watts):	30W
LED Quantity (per mtr):	1
LED Classification:	Superlight MX LED Engine
Recommend Ambient Temp:	-40°C ~ +55°C
Fitting Construction:	Die Cast Aluminium
Luminous Flux:	1900 Lumens
Standard Viewing/Beam Angle:	110°
Power Factor:	>0.98
Power Efficiency:	>85%
Colour Rendering Index:	RA >85
Energy Consumption Rating:	Low
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

SL9003-15 CCT: 6500K CRI: >80

SL9003-21 CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

The 30W MX LED floodlight is ideally suited to replace standard floodlights up to 150W and is suitable for all general purpose floodlighting such as commercial security floodlighting, car parks, hotels etc.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL9003-15	30W LED Area Floodlight 240V COOL WHITE
SL9003-21	30W LED Area Floodlight 240V WARM WHITE

CUSTOMISATION OPTIONS

Fixture colour can be refinished

Custom RGB version available by special request

24VDC DMX dimmable version available by special request

Customisation options are subject to availability and minimum order quantities



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.