



SUPERLIGHT FL7200 LED FLOODLIGHT 200W DIMMABLE

Superlight FL7 is a new generation LED floodlight with integrated mains voltage LED module. FL7 delivers superior lumen output with optimum efficiency. The fittings are manufactured from robust materials and can be used in any Industrial, commercial or residential environment. FL7 is dimmable using most regular style phase dimmers. Optional Casambi wireless or DALI control also available.

SPECIFICATIONS

Input Voltage:	85-285VAC
Dimensions (W x H x D):	460x330x177mm
Max Power Consumption:	200W
Electrical Insulation Class:	Class I
LED Classification:	Osram 2020T
Recommend Ambient Temp:	-40°C ~ +55°C
Fitting Construction:	Aluminium & Corrosion Resistant
Typical Light Source Efficacy	135lm/W
Standard Viewing/Beam Angle:	120°
Power Factor:	>0.98
Minimum IK Rating	IK09
Colour Rendering Index:	RA >85 / RA>90
Standard Dimming Config:	Phase Dimmable
IP Protection Rating:	IP65



PHOTOMETRIC INFORMATION

FL7200-15	CCT: 6500K CRI: >85
FL7200-17	CCT: 3000K CRI: >85
FL7200-21	CCT: 3000K CRI: >90


Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Ideally suited for high end washing applications such as nightclubs wall-washing, architectural lighting, hotels, plazas, corporate colour-schemes, special events, venues & productions etc.

CONTROL & DIMMING COMPATIBILITY

FL7 is dimmable and is compatible with regular style Phase Dimmers. Optional control via DALI, 1-10V, DMX512 is available by special request. .Please contact us for options and availability.



ORDERING INFORMATION

FL7200-15	FL7 LED FLOODLIGHT 86-265VAC 200W DIMMABLE 6500k
FL7200-17	FL7 LED FLOODLIGHT 86-265VAC 200W DIMMABLE 4000k
FL7200-21	FL7 LED FLOODLIGHT 86-265VAC 200W DIMMABLE 3000k

CUSTOMISATION OPTIONS

Finish/colour can be refinished by request

RGBW version available by special request

DALI version available by special request

Available in other variants from  by special request

via Casambi Wireless option by special request

Customisation options may be subject to availability and minimum order quantities

CASAMBI



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.