

## SUPERLIGHT DCR4410 ARCHITECTURAL PRISMATIC LED HIGHBAY

Superlight DCR4410 is a modern industrial highbay luminaire with metallic finish and high performance thermal management and powerful light source components. The finish and characteristics can be customised to suit a range of projects and applications. LED highbay pendant with coded canopy, prismatic refractor and integrated LED. Control gear is integrated. Dimmable options available by request.

### SPECIFICATIONS

Model Number:	DCR4410 Prismatic Refractor
Input Voltage:	85-265VAC
Power Consumption:	30W / 60W / 80W / 120W
Diameter:	410mm
Overall Height:	540mm
Fixture Material:	Anodised Aluminum + Polycarbonate
Standard Colour Finish:	Metallic Silver / Prismatic
LED Classification:	Shard COB CXA
Light Source Efficacy:	115lm/W
Light Source CRI:	>85
Beam Angle:	90-120°
Ambient Temp:	-20 ~ +45°C
IP Protection Rating:	IP44



### PHOTOMETRIC INFORMATION

DCR4410	CCT: 6500K CRI: >85	90-120°
DCR4410	CCT: 4000K CRI: >85	90-120°
DCR4410	CCT: 3000K CRI: >85	90-120°

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Supermarket, retail and shopping areas, highbay lighting, area lighting, landscape illumination, highbay lighting, warehouses, architectural lighting, commercial interiors, wall washing, security lighting, public spaces, education facilities, hotels and hospitality projects, office lighting, showroom lighting.

### CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Casambi wireless control by request. Please contact us for options and availability.

### ORDERING INFORMATION

DCR4410W30	Superlight Architectural Highbay Luminaire 30W
DCR4410W60	Superlight Architectural Highbay Luminaire 60W
DCR4410W80	Superlight Architectural Highbay Luminaire 80W
DCR4410W100	Superlight Architectural Highbay Luminaire 100W

Specify CCT Colour Temperature 2700K / 3000K / 4000K / 6000K

Specify Dimming Option: Non Dimmable / Phase Dimmable / DALI / Wireless

### CUSTOMISATION OPTIONS

- Custom wattage option by request.
- Available with solid acrylic (colour optional) reflector
- Supplied with 1.5mtr suspension - can be customised by request
- Optional mounting bracket options available by special request

Minimum order quantities may apply for some custom options

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

