

SL2478 MARINE SERIES STAINLESS STEEL LED FITTING

The Superlight SL2478 is a stainless steel light fitting suitable for recess mounting for a variety of interior and exterior projects. Typical applications including uplighting, marine installations, exterior lighting and task lighting. The fitting is constructed from solid 316 stainless steel.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	1.0W
Trim Dimensions:	30mm Diameter
Cutout Dimensions:	25mm
Fitting Depth:	44mm
LED Classification:	CREE
LED Quantity:	1
Lens Configuration	Frosted Lens
Construction Material:	Solid Stainless Steel
Stainless Steel Grade:	316 Marine Grade Stainless Steel
Typical Light Source Efficacy:	85lm/W
Beam Angle:	120°
Recommended Ambient Temp:	-15 ~ +50°C
IP Protection Rating:	IP67

PHOTOMETRIC INFORMATION

SL2478-15	CCT: 6000K CRI: 80
SL2478-17	CCT: 4000K CRI: 80
SL2478-15	CCT: 3000K CRI: 80
SL2478-35	RGB

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Marine applications, outdoor lighting, feature lighting, decorative installations, luxury marine vessels, landscape lighting, deck lighting, pathways, steplighting, display cases, niches, garden lighting.

CONTROL & DIMMING COMPATIBILITY

Superlight SL2478 fittings are dimmable and can be controlled vis any Superlight constant voltage dimming controller, including Superlight 1-10V Analogue, DALI, or DMX512

RGB version is controllable with any Superlight 12/24VDC Colour Controller

ORDERING INFORMATION

SL2478-21	Marine Series SS316 Round Mini Light 30mm 3000K
SL2478-17	Marine Series SS316 Round Mini Light 30mm 4000K
SL2478-15	Marine Series SS316 Round Mini Light 30mm 6000K
SL2478-35	Marine Series SS316 Round Mini Light 30mm RGB

CUSTOMISATION OPTIONS

Fixture can be powdercoated by special request

Superlight can design and supply dimming control or RGB control systems

**Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

