

SL2556 WDL UP & DOWN LED WALL LIGHT

Superlight SL2556 up & down LED wall mounted light fittings are suitable for large scale commercial and industrial projects that require high-performance illumination. The fixtures incorporate integral constant current LED driver and are protected to IP65 making them suitable for any interior or exterior environment.

SPECIFICATIONS

Input Voltage:	100-265VAC
LED Driver Configuration:	Integral, Constant Current
Power Consumption:	2x26W or 2x39W
Body Diameter	180mm
Overall Height:	350mm
Overall Width:	240mm
Fixture Material:	Extruded Alloy/Powdercoated
Standard Colour Finishes	Black or Matt Grey
LED Classification:	XP-E LED
Typical Light Source Efficacy:	95lm/W
Light Source CRI:	>85
Beam Angle Options:	2x24°
Recommended Ambient Temp:	-20 ~ +45°C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

SL2556	CCT: 6500K CRI: >85
SL2556	CCT: 4200K CRI: >85
SL2556	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial exterior lighting, facade lighting, pillar and column highlighting , hospitality projects, industrial projects, retail environments, warehouse and industrial projects.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL2556**39W-3200K WDL556 Up&Down LED Wall Light 100-265VAC 2x39W
SL2556**39W-4200K WDL556 Up&Down LED Wall Light 100-265VAC 2x39W
SL2556**39W-6500K WDL556 Up&Down LED Wall Light 100-265VAC 2x39W
SL2556**26W-3200K WDL556 Up&Down LED Wall Light 100-265VAC 2x26W
SL2556**26W-4200K WDL556 Up&Down LED Wall Light 100-265VAC 2x26W
SL2556**26W-6500K WDL556 Up&Down LED Wall Light 100-265VAC 2x26W
**Specify fixture colour Black = BK / Matt Grey = GY

CUSTOMISATION OPTIONS

Optional 24VDC version available by special request
Fixture colour can be refinished by special request
Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

