

## SL2833 Nexus DL15 Surface Mount LED Downlight

Superlight Nexus DL15 is an integrated surface mounted LED downlight. The fitting incorporates integral LED control gear and high quality polished specular reflector. Superlight Nexus DL15 fittings are ideally suited to residential and commercial projects that require a high performance surface mounted solution.

### SPECIFICATIONS

Input Voltage:	220-240VAC
Max Power Consumption:	15W
Diameter:	90mm
Fixture Height:	100mm
LED Classification:	Sharp COB
LED Quantity:	1
LED Drive Current:	360mA
LED Light Source CRI	>85Ra / >90Ra
Colour/Finish:	White / Black
Fixture Material:	Aluminium
Typical Light Source Efficacy:	100lm/W
Beam Angle:	60°
Recommended Ambient Temp:	-20 ~ +45°C
Net Weight:	1.3KG
IP Protection Rating:	IP54



CASAMBI



### PHOTOMETRIC INFORMATION

SL2833	CCT: 6000K CRI: >85
SL2833	CCT: 4000K CRI: >85
SL2833	CCT: 3000K CRI: >85
SL2833	CCT: 2700K CRI: >85



Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Hotels, hospitality projects, retail and showroom lighting, concrete slab lighting, commercial projects, stairwell, foyers, reception areas, offices, common areas, residential projects, awnings and outdoor lighting.


### CONTROL & DIMMING COMPATIBILITY

Superlight DL15 LED fittings are supplied with phase control dimmable LED drivers  
Optional DALI dimmable LED driver is available by special request  
Optional 1-10V dimmable LED driver is available by special request

### ORDERING INFORMATION

SL2833WH-21	Nexus DL15 Surf Mount Downlight White Dimmable 3000K
SL2833WH-17	Nexus DL15 Surf Mount Downlight White Dimmable 4000K
SL2833WH-15	Nexus DL15 Surf Mount Downlight White Dimmable 5700K
SL2833BK-21	Nexus DL15 Surf Mount Downlight Black Dimmable 3000K
SL2833BK-17	Nexus DL15 Surf Mount Downlight Black Dimmable 4000K
SL2833BK-15	Nexus DL15 Surf Mount Downlight Black Dimmable 5700K

### CUSTOMISATION OPTIONS



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.