

SL2834 NEXUS DL25 SURFACE MOUNT LED DOWNLIGHT

Superlight Nexus DL25 is an integrated surface mounted LED downlight. The fitting incorporates integral LED control gear and high quality polished specular reflector. Superlight Nexus DL25 fittings are ideally suited to residential and commercial projects that require a high performance surface mounted solution.

SPECIFICATIONS

Input Voltage:	220-240VAC
Max Power Consumption:	25W
Diameter:	120mm
Fixture Height:	110mm
LED Classification:	Sharp COB
LED Quantity:	1
LED Drive Current:	600mA
LED Light Source CRI	>80Ra
Colour/Finish:	White / Black
Fixture Material:	Aluminium
Typical Light Source Efficacy:	100lm/W
Beam Angle:	60°
Recommended Ambient Temp:	-20 ~ +45°C
Net Weight:	1.3KG
IP Protection Rating:	IP54



PHOTOMETRIC INFORMATION

SL2834	CCT: 6000K CRI: >85
SL2834	CCT: 4000K CRI: >85
SL2834	CCT: 3000K CRI: >85
SL2834	CCT: 2700K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Hotels, hospitality projects, retail and showroom lighting, concrete slab lighting, commercial projects, stairwell, foyers, reception areas, offices, common areas, residential projects, awnings and outdoor lighting.

CONTROL & DIMMING COMPATIBILITY

Superlight DL25 LED fittings are supplied with phase control dimmable LED drivers
Optional DALI dimmable LED driver is available by special request
Optional 1-10V dimmable LED driver is available by special request

ORDERING INFORMATION

SL2834WH-21	Nexus DL25 Surf Mount Downlight White Dimmable 3000K
SL2834WH-17	Nexus DL25 Surf Mount Downlight White Dimmable 4000K
SL2834WH-15	Nexus DL25 Surf Mount Downlight White Dimmable 5700K
SL2834BK-21	Nexus DL25 Surf Mount Downlight Black Dimmable 3000K
SL2834BK-17	Nexus DL25 Surf Mount Downlight Black Dimmable 4000K
SL2834BK-15	Nexus DL25 Surf Mount Downlight Black Dimmable 5700K

CUSTOMISATION OPTIONS

Fixture colour options Black or White

Colour can be refinished by special request

DALI dimmable version available by special request

**Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.