

RAM SL3672 RECESSED EXTERIOR LED WALL LIGHT

Superlight Ram SL3672 is a high grade exterior light fitting suitable for recessed installation. The fitting incorporates integrated Osram LED and control gear and is suited to architectural environments to provide functional and efficient illumination. The Ram series is ideal for pathways, passageways, stairways, public spaces and other task lighting applications.

SPECIFICATIONS

Input Voltage:	100-240VAC
Max Power Consumption:	6W
Trim Dimensions:	85x220mm
Overall Fixture Depth:	79mm
LED Classification:	Osram Optoelectronic
LED Quantity:	1
Colour/Finish:	Corrosion Resistant Powdercoat Finish
Typical Light Source Efficacy:	80lm/W
Beam Angle Options:	100°
Included Accessories:	Mounting Box Included
Recommended Ambient Temp::	-10 ~ +40°C
IP Protection Rating:	IP65

PHOTOMETRIC INFORMATION

SL3672-15	CCT: 6000K CRI: >80
SL3672-17	CCT: 4200K CRI: >80
SL3672-21	CCT: 3000K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include commercial and residential lighting, public spaces, pathways and passageways, stairwell lighting, retaining walls, entrances and common areas, hotels, hospitality projects etc.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512.

ORDERING INFORMATION

SL3672-15	Recessed Wall Light Silver 220x85mm inc Housing 6000K
SL3672-17	Recessed Wall Light Silver 220x85mm inc Housing 4200K
SL3672-21	Recessed Wall Light Silver 220x85mm inc Housing 3000K
SL3672BK-15	Recessed Wall Light Black 220x85mm inc Housing 6000K
SL3672BK-17	Recessed Wall Light Black 220x85mm inc Housing 4200K
SL3672BK-21	Recessed Wall Light Black 220x85mm inc Housing 3000K

CUSTOMISATION OPTIONS

Standard powdercoat finishes including Black or Silver

Fixture colour can be refinished by special request

**Custom options may be subject to minimum order quantities



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.