

SL3698 EXTERIOR LED WALL/STEPLIGHT

The Superlight 3698 recessed LED wall fittings are IP65 rated for all indoor/outdoor areas and are great for residential and commercial projects because they consume very little energy and require zero lamp maintenance. The fittings have solid 316 marine grade stainless steel trim and frosted lens.

SPECIFICATIONS

Input Voltage:	240V
Max Power Consumption:	6W
LED Quantity:	25
LED Classification:	SSC High Brightness SMD
Standard Viewing Angle:	60°
Trim Construction:	Solid 316 Marine Grade Stainless Steel
Trim Dimensions:	124mm x 124mm
Fitting Depth:	79mm
Mounting Housing Included:	Yes
Operating Temperature:	-10°C ~ +65°C
Weight:	1.3Kg
IP Protection Rating:	IP65



PHOTOMETRIC INFORMATION

SL3698-11	Typical Wavelength: RED 650nm
SL3698-12	Typical Wavelength: GREEN 560nm
SL3698-13	Typical Wavelength: BLUE 450nm
SL3698-15	CCT: 6500K CRI: >70
SL3698-21	CCT: 3200K CRI: >75

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial & residential landscape lighting, Exterior steplighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL3698-11	IP65 Recessed LED Wall Light RED
SL3698-12	IP65 Recessed LED Wall Light GREEN
SL3698-13	IP65 Recessed LED Wall Light BLUE
SL3698-14	IP65 Recessed LED Wall Light AMBER
SL3698-15	IP65 Recessed LED Wall Light COOL WHITE

CUSTOMISATION OPTIONS

Trim Colour can be refinished

12/24VDC RGB version also available

Low voltage conversion available by request

Customisation options are subject to availability and minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.