

SUPERLIGHT LIDO-120 INGROUND LINEAR LED FIXTURE

Superlight Lido-120 series is a high quality linear LED fixture suitable for inground installations. The fixtures are ideal for facade lighting and architectural feature lighting for commercial projects. The fixtures incorporate high-grade tempered glass lens and stainless steel trim.

SPECIFICATIONS

Model:	Lido-120 Series (120° Optic)
Input Voltage:	100-240VAC
Power Consumption:	6W-32W
Nominal Lengths Available:	350mm/650mm/920mm
Overall Width:	110mm
Overall Depth:	120mm
Fixture Materials:	Stainless Steel and Glass
Included Accessories:	Mounting Housing
LED Classification:	XP-E / 3528SMD LED
Typical Light Source Efficacy:	110lm/W
Light Source CRI:	>85
Beam Angle:	120°
Recommended Ambient Temp:	-35 ~ +55°C
IP Protection Rating:	IP67

PHOTOMETRIC INFORMATION

SL4062 Lido-120	CCT: 5700K CRI: >85
SL4062 Lido-120	CCT: 4000K CRI: >85
SL4062 Lido-120	CCT: 3000K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Exterior inground lighting, uplighting, signage & billboards, public spaces, streetscapes, landscape lighting, parks and recreation, retail environments, hotels & hospitality projects, industrial lighting, trafficable areas.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL4062K120	Lido Inground XPE Linear Fixture 350mm 120deg 10.8W
SL4063K120	Lido Inground XPE Linear Fixture 650mm 120deg 21.6W
SL4064K120	Lido Inground XPE Linear Fixture 920mm 120deg 32.4W
SL4062SMD120	Lido Inground SMD Linear Fixture 350mm 120deg 6W
SL4063SMD120	Lido Inground SMD Linear Fixture 650mm 120deg 13W
SL4064SMD120	Lido Inground SMD Linear Fixture 920mm 120deg 18W

** Specify beam angle 12° / 24° / 36° / 12°x30°

CUSTOMISATION OPTIONS

Superlight Lido series is also available with narrow beam optics
Stainless steel trim can be refinished by special request
24VDC version available by special request
Minimum order quantities apply for custom options

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

