

SL4167 STAINLESS STEEL LED DOWNLIGHT

Superlight SL4167 is a high quality marine grade LED downlight suitable for all types of projects including harsh & hazardous environments. The downlight body is constructed from stabilised polycarbonate and features genuine 316 stainless steel trim with tempered glass lens.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	16W
Trim Diameter:	186mm
Ceiling Cutout:	170mm
LED Classification:	Superlight COB
LED Quantity:	1
Colour/Finish:	Brushed Stainless Steel
Fixture Material:	316 Stainless Steel Marine Grade
Typical Light Source Efficacy:	85lm/W
Beam Angle Options:	30° / 60°
Recommended Ambient Temp:	-20 ~ +50°C
IP Protection Rating:	IP67

PHOTOMETRIC INFORMATION

SL4167-15	CCT: 5600K CRI: >80
SL4167-17	CCT: 4200K CRI: >80
SL4167-21	CCT: 3000K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include exterior lighting, wet areas, marine locations, harsh environments, hazardous locations, retail & hospitality projects, industrial projects.

CONTROL & DIMMING COMPATIBILITY

Superlight SL4167 downlight features an integral phase-dimmable LED driver. The fitting is compatible with most universal style phase control dimmers

ORDERING INFORMATION

SL4167-15	Superlight 316 Stainless Steel LED Downlight 60° 5600K
SL4167-17	Superlight 316 Stainless Steel LED Downlight 60° 4200K
SL4167-21	Superlight 316 Stainless Steel LED Downlight 60° 3000K
SL4167D30-15	Superlight 316 Stainless Steel LED Downlight 30° 5600K
SL4167D30-17	Superlight 316 Stainless Steel LED Downlight 30° 4200K
SL4167D30-21	Superlight 316 Stainless Steel LED Downlight 30° 3000K

CUSTOMISATION OPTIONS

Stainless steel trim can be refinished by special request

Optional remote DALI dimmable driver by request

** Custom options may be subject to minimum order quantities

