

SUPERLIGHT SL500-15D GUNMETAL LED LANDSCAPE FIXTURE

The Superlight Gunmetal series is a professional range of LED lighting fixtures which for use within commercial projects, architectural illumination and landscapes. SL500 features a stylish design, robust construction and adjustable mounting bracket or yoke-mount option.

SPECIFICATIONS

Series Model Number:	SL500Y15D	SL500U15D
Mounting Bracket:	Y Bracket	U Bracket
Input Voltage:	90-265VAC	90-265VAC
Power Consumption:	28W	28W
Face Dimensions:	362x127	362x127
Body Depth:	146mm	146mm
Overall Height:	165mm	165mm
Fixture Material:	Magnesium Alloy	Magnesium Alloy
LED Classification:	CREE XP LED	CREE XP LED
LED Qty:	15	15
Typical Light Source Efficacy:	90lm/W	90lm/W
Beam Angle Options:	6° / 15° / 30° / 48°	6° / 15° / 30° / 48°
RGB Option:	24VDC with DMX512	24VDC with DMX512
Recommended Ambient Temp:	-15 ~ +55°C	-15 ~ +55°C
IK Impact Protection Rating:	>IK08	>IK08
IP Protection Rating:	IP66	IP66

PHOTOMETRIC INFORMATION

SL500*15D-6500K	CCT: 6500K CRI: >85
SL500*15D-4000K	CCT: 4000K CRI: >85
SL500*15D-3000K	CCT: 3000K CRI: >85
SL500*15D-RGB	RGB 24VDC with DMX

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include landscape and feature lighting, sculptures and flagpole illumination, garden lighting and architectural highlighting.

CONTROL & DIMMING COMPATIBILITY

Superlight SL500 fittings can be fitted with integral dimming control gear by special request. RGB+DMX configuration available. RGB fitting is supplied with integral DMX decoder.

ORDERING INFORMATION

SL500*15D-3000K Superlight SR500 LED Landscape Spotlight/Projector
SL500*15D-4000K Superlight SR500 LED Landscape Spotlight/Projector
SL500*15D-6500K Superlight SR500 LED Landscape Spotlight/Projector
SL500*15D-RGB Superlight SR500 LED Landscape Spotlight/Projector

**Specify mounting bracket type: Y Bracket or U Bracket

**Specify input voltage option: 100-240VAC or 24VDC (RGB Option)

**Specify beam angle option: 6° / 15° / 30° / 48°

CUSTOMISATION OPTIONS

Fixture colour can be refinished

DALI dimmable options available by special request

Vandal resistant protective steel cage available by special request

Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

