

SL600U GUNMETAL LED SPOTLIGHT/PROJECTOR

Superlight Gunmetal series is a professional range of LED lighting fixtures which for use within commercial projects, architectural illumination and landscapes. SL600U features a stylish design, robust construction and adjustable mounting bracket. LED configurations include options up 30W & other configuration options are available.

SPECIFICATIONS

Series Model Number:	SL600UA-	SL600UD-
Input Voltage:	100-240VAC	12VDC
Power Consumption:	21W/30W	21W/30W
Body Diameter:	163mm	163mm
Body Length:	180mm	180mm
Overall Height:	230mm	230mm
Fixture Material:	Magnesium Alloy	Magnesium Alloy
LED Classification:	CREE XP-E	CREE XP-E
Typical Light Source Efficacy:	90lm/W	90lm/W
Beam Angle Options:	5° / 15° / 30° / 45°	5° / 15° / 30° / 45°
RGB Option:	Int DMX Decoder	Int DMX Decoder
Recommended Ambient Temp:	-15 ~ +55°C	-15 ~ +55°C
IK Impact Protection Rating:	>IK08	>IK08
IP Protection Rating:	IP66	IP66

PHOTOMETRIC INFORMATION

SL600U**6500K	CCT: 6500K CRI: >85
SL600U**4000K	CCT: 4000K CRI: >85
SL600U**3000K	CCT: 3000K CRI: >85
SL600U**RGB	RGB with DMX

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Typical applications include landscape and feature lighting, sculptures and flagpole illumination, garden lighting and architectural highlighting.

CONTROL & DIMMING COMPATIBILITY

Superlight SL600 fittings can be fitted with integral dimming control gear by special request. RGB+DMX configuration available. RGB fitting is supplied with integral DMX decoder.

ORDERING INFORMATION

SL600U**-3000K	Superlight SL600U LED Landscape Spotlight/Projector
SL600U**-4000K	Superlight SL600U LED Landscape Spotlight/Projector
SL600U**-6500K	Superlight SL600U LED Landscape Spotlight/Projector
SL600U**-RGB	Superlight SL600U LED Landscape Spotlight/Projector

CUSTOMISATION OPTIONS

Fixture colour can be refinished
DALI dimmable options available by special request
Y-Bracket (yoke) mounting option available by special request
Vandal resistant protective steel cage available by special request
Custom options may be subject to minimum order quantities

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

