

SL6332 SUPERLIGHT EXTERIOR WALL MOUNTED LED DOWNLIGHT

Superlight SL6332 is a high quality wall mounted downlight which can be used for exterior and interior applications. The product features integral LED driver and high efficiency LED Module. The fitting has a high grade powdercoated finish and is available in either Silver or Black. Other colours/finishes are available by request.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	3W
Body Diameter:	80mm
Overall Height:	136mm
LED Classification:	Edison XRLED
Available Colour/Finishes:	Matt Silver / Matt Black
Typical Efficacy:	80lm/W
LED Beam Angle:	30°
Fixture Material:	Powdercoated Alloy
Recommended Ambient Temp:	-10°C~+40°C
IP Protection Rating:	IP54

PHOTOMETRIC INFORMATION

SL6332-15	CCT: 6000K CRI: >80
SL6332-17	CCT: 4000K CRI: >80
SL6332-21	CCT: 3000K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Exterior landscape lighting, Pillar and column lighting, Feature spotlighting, Courtyards and dining areas, Hotels and hospitality projects

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL6332GY-21	Superlight Exterior Wall Mounted LED GREY 3000K
SL6332GY-17	Superlight Exterior Wall Mounted LED GREY 4000K
SL6332GY-15	Superlight Exterior Wall Mounted LED GREY 6000K
SL6332BK-21	Superlight Exterior Wall Mounted LED BLACK 3000K
SL6332BK-17	Superlight Exterior Wall Mounted LED BLACK 4000K
SL6332BK-15	Superlight Exterior Wall Mounted LED BLACK 6000K

CUSTOMISATION OPTIONS

Fixture colour can be refinished by special request

