

SL6342 SUPERLIGHT EXTERIOR WALL MOUNTED LED DOWNLIGHT

Superlight SL6342 is a high quality wall mounted downlight which can be used for exterior and interior applications. The product features integral LED driver and high efficiency LED Module. The fitting has a high grade powdercoated finish and is available in either Silver or Black. Other colours/finishes are available by request.

SPECIFICATIONS

Input Voltage:	100-240VAC
Power Consumption:	3W
Body Diameter:	60mm
Overall Height:	120mm
LED Classification:	Edison XRLED
Available Colour/Finishes:	Matt Silver / Matt Black
Typical Efficacy:	80lm/W
LED Beam Angle:	30°
Fixture Material:	Powdercoated Alloy
Recommended Ambient Temp:	-10°C~+40°C
IP Protection Rating:	IP54

PHOTOMETRIC INFORMATION

SL6342-15	CCT: 6000K CRI: >80
SL6342-17	CCT: 4000K CRI: >80
SL6342-21	CCT: 3000K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Exterior landscape lighting, Pillar and column lighting, Feature spotlighting, Courtyards and dining areas, Hotels and hospitality projects

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL6342GY-21	Superlight Exterior Wall Mounted LED GREY 3000K
SL6342GY-17	Superlight Exterior Wall Mounted LED GREY 4000K
SL6342GY-15	Superlight Exterior Wall Mounted LED GREY 6000K
SL6342BK-21	Superlight Exterior Wall Mounted LED BLACK 3000K
SL6342BK-17	Superlight Exterior Wall Mounted LED BLACK 4000K
SL6342BK-15	Superlight Exterior Wall Mounted LED BLACK 6000K

CUSTOMISATION OPTIONS

Fixture colour can be refinished by special request



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.