

SL6492 OVOID LED WALL LIGHT FIXTURE

Superlight Ovoid LED Wall Light fittings feature a contemporary curved shell design and offer a sleek and modern solution to any decor. The fittings have integral LED driver and matt bronze internal reflector.

SPECIFICATIONS

Input Voltage:	24VDC
Max Power Consumption:	6W
LED Quantity:	2 x 3W
LED Classification:	X-LED
LED Beam Angle:	90°
Fixture Dimensions Height:	160mm Height
Fixture Dimensions Width:	155mm Width
Fixture Dimensions Depth:	105mm Depth
Depth of Mounting Can:	110mm
Driver Integral:	Yes
Dimmable:	Not Dimmable
Recommended Ambient Temp:	-5 ~ +55°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL6492-15	CCT: 6500K CRI: >80
SL6492-21	CCT: 3200K CRI: >85

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Commercial and residential interior applications, Decorative & architectural lighting, Common area lighting, Cinemas and theatres

CONTROL & DIMMING COMPATIBILITY

SL6492 LED Wall Lights are supplied with non dimmable LED driver.
Optional DALI dimmable LED driver are available by request.

ORDERING INFORMATION

SL6492-15	6W Ovoid LED Wall Light 6500K COOL WHITE
SL6492-21	6W Ovoid LED Wall Light 3200K WARM WHITE

CUSTOMISATION OPTIONS

Fixture colour can be refinished
Optional remote DALI dimmable controller option
Customisation options are subject to availability and minimum order quantities

