

SL7209 SUPERLIGHT VRX LED STRIPLIGHTING 9.6W

Superlight VRX LED strip is an advanced LED product, designed and manufactured exclusively by Superlight. The product features a brand new LED classification which delivers extremely high light output with exceptional stability and CRI. Superlight VRX LED Strip sets a new benchmark for the quality and performance of linear LED lighting.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	9.6W per mtr
Dimensions:	5mm Width
LED Spacing:	8.3mm
LED Qty:	120
Smallest Cutting Increment:	50mm
LED Classification:	VRX-22
LED CRI:	>95
Typical Light Source Efficacy:	130lm/W
Viewing Angle:	120°
Max Recommended Single Length:	10mtrs
Recommended Ambient Temp:	-15°C~+50°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL7209-15	CCT: 6500K CRI: >95
SL7209-17	CCT: 4200K CRI: >95
SL7209-21	CCT: 3200K CRI: >95
SL7209-27	CCT: 2700K CRI: >95
SL7209-22	CCT: 2200K CRI: >90

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

VRX LED strip is designed for high end projects where quality, reliability and exceptional performance is desired. Applications include concealed lighting, joinery, feature lighting, backlighting, linear lighting, continuous mounting profiles etc.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL7209-2200K	Superlight VRX22 LED Strip 9.6W per mtr 12VDC
SL7209-2700K	Superlight VRX22 LED Strip 9.6W per mtr 12VDC
SL7209-3200K	Superlight VRX22 LED Strip 9.6W per mtr 12VDC
SL7209-4200K	Superlight VRX22 LED Strip 9.6W per mtr 12VDC
SL7209-6500K	Superlight VRX22 LED Strip 9.6W per mtr 12VDC

CUSTOMISATION OPTIONS

Dimmable via Superlight dimming controllers including DALI / DMX / 1-10V
Superlight can supply customised lengths to site requirements
Several aluminium mounting profiles available
Superlight can design and manufacture a full linear lighting solution for any project
Custom 24VDC version available by special request

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

