

SL7455 STREAMLINE-XR LINKABLE LINEAR LED

Superlight Streamline-XR is a convenient linkable linear LED lighting product that can be used for a variety of applications. Streamline-XR is designed with a unique edgeview LED orientation which delivers smooth and uniform illumination. Superlight Streamline products allow for seamless linkable continuous installations, requiring no soldering cutting or modifications. Superlight offers a range of linkable accessories allowing the product to be used in almost any configuration.

SPECIFICATIONS

Input Voltage:	24VDC
Power Consumption:	2.5W / 5W / 9W / 14W / 15W / 17W
Lengths:	150/300/600/900/1000/1200mm
Profile Dimensions:	30x13mm
LED Classification:	SSC SMD LED
LED Orientation:	Side/Edgeview
Typical Light Source Efficacy:	80lm/W
Viewing Angle:	100°
Max Recommended Continuous Length:	6mtrs
Recommended Ambient Temp:	-20°C~+50°C
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL7455	CCT: 6000K CRI: >84
SL7455	CCT: 4000K CRI: >88
SL7455	CCT: 3000K CRI: >88

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Applications include joinery lighting, display cabinets, showcases, indirect lighting, concealed lighting, pelmet and coffer lighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL7455	Superlight Streamline Express LED 150mm 2.5W
SL7455	Superlight Streamline Express LED 300mm 5W
SL7455	Superlight Streamline Express LED 600mm 9W
SL7455	Superlight Streamline Express LED 900mm 14W
SL7455	Superlight Streamline Express LED 1000mm 15W
SL7455	Superlight Streamline Express LED 1200mm 17W

** Specify CCT Colour Temperature: 3000K/4000K/6000K

** Specify installation accessories

CUSTOMISATION OPTIONS

Various mounting and connection accessories available
Superlight can design mounting accessories by special request
DALI dimmable controller available by request



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.