

## SL7466 STREAMLINE EXPRESS LINKABLE LINEAR LED

Superlight Streamline Express is an economical and convenient linear LED lighting product that can be used for a variety of applications. The Streamline fittings are linkable for seamless continuous installations, requiring no soldering cutting or modifications. Superlight offers a range of linkable accessories allowing the product to be used in almost any configuration.

### SPECIFICATIONS

Input Voltage:	24VDC
Power Consumption:	2.5W / 5W / 9W / 14W / 15W / 17W
Lengths:	150/300/600/900/1000/1200mm
Profile Dimensions:	18x8mm
LED Classification:	SSC SMD LED
Typical Light Source Efficacy:	80lm/W
Viewing Angle:	100°
Max Recommended Continuous Length:	6mtrs
Recommended Ambient Temp:	-20°C~+50°C
IP Protection Rating:	IP20

### PHOTOMETRIC INFORMATION

SL7466	CCT: 6000K CRI: >84
SL7466	CCT: 4000K CRI: >88
SL7466	CCT: 3000K CRI: >88

Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Applications include joinery lighting, display cabinets, showcases, indirect lighting, concealed lighting, pelmet and coffer lighting.

### CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

### ORDERING INFORMATION

SL7466	Superlight Streamline Express LED 150mm 2.5W
SL7466	Superlight Streamline Express LED 300mm 5W
SL7466	Superlight Streamline Express LED 600mm 9W
SL7466	Superlight Streamline Express LED 900mm 14W
SL7466	Superlight Streamline Express LED 1000mm 15W
SL7466	Superlight Streamline Express LED 1200mm 17W

\*\* Specify CCT Colour Temperature: 3000K/4000K/6000K

\*\* Specify installation accessories

### CUSTOMISATION OPTIONS

Various mounting and connection accessories available

Superlight can design mounting accessories by special request

DALI dimmable controller available by request

