

SL7605 GEN2 LED Turbostrip

Superlight Generation-2 LED Turbostrip is an extremely versatile linear lighting system suitable for all types of concealed, indirect & joinery lighting. Superlight Generation-2 LED Turbostrip incorporates class leading Micro-SMD LED technology for optimum performance and efficiency.

SPECIFICATIONS

Input Voltage:	12VDC
Max Power Consumption:	13W per mtr
LED Classification:	Generation 2 SSC SMD V-LED
Typical LED Efficacy:	85lm/W
Viewing Angle:	120°
Standard Length:	Superlight can supply any length
Max Recommended Single Length:	10 mtrs
Recommended Ambient Temperature:	-5°C ~ +55°C
Recommended Heatsink:	SL8900 or HLP4110 Mounting Profile
IP Protection Rating:	IP20

PHOTOMETRIC INFORMATION

SL7605-27	CCT: 2700K CRI: >80
SL7605-21	CCT: 3200K CRI: >85
SL7605-17	CCT: 4200K CRI: >85
SL7605-15	CCT: 6500K CRI: >87

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Kitchen & Bathroom Lighting, Concealed Joinery Lighting, Ceiling Coffe Light-ing, Bulkhead & Pelmet Lighting, Continuous Feature Lighting, High Output Linear Lighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL7605-27	GEN2 LED Turbostrip 12VDC Warm White 2700K
SL7605-21	GEN2 LED Turbostrip 12VDC Warm White 3200K
SL7605-42	GEN2 LED Turbostrip 12VDC Neutral White 4200K
SL7605-15	GEN2 LED Turbostrip 12VDC Cool White 6500K

** Specify Beam angle: 15° / 24°

CUSTOMISATION OPTIONS

Supplied in custom lengths

Superlight Turbostrip is manufactured to any desired length and can be supplied fully-assembled or in component form for assembly on site.



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.