

SL8900 LINEAR LED LIGHTING PROFILE

Our special purpose LED mounting track has been especially designed to suit our flexible LED striplighting products. The mounting track has a very slim profile and can be incorporated into any architectural project to provide a professional finish.

The track can be anodised, chrome-plated or powdercoated to suit any decorative environment. Supplied with either clear or opal acrylic lens diffuser. Popular applications include kitchen & bathroom lighting, task lighting, recessed joinery lighting.

SPECIFICATIONS

Standard Profile Length:	3.2mtr
Custom Lengths Available:	Yes
Profile Dimensions (W x H):	20 x 8 mm
Standard Finish:	Satin Aluminium
Optional Colours/Finishes:	Dulux Powdercoat or Anodised
Suitable LED Product:	LED Turbostrip or LED Superstrip
Lens Options:	Clear or Opal Acrylic Lens
Optional Lens Available:	Toughened Polycarbonate
Weight:	Approx 0.14Kg per mtr



PHOTOMETRIC INFORMATION

Detailed photometric reports are available by request
Superlight can provide wiring schematics and lighting control system design.
Contact us for more information.

Detailed photometric report and IES files available. Contact Superlight for more information. LM80, LM79 test reports available by request.

TYPICAL APPLICATIONS

Popular applications include kitchen & bathroom lighting, task lighting, recessed joinery lighting.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL8900-00	8900 Series LED Mounting Track
SL8900-12	Opal Acrylic Lens To Suit
SL8900-14	Clear Acrylic Lens To Suit
SL8900-16	Toughened Opal Polycarbonate Lens To Suit
SL8900-55	Clear Acrylic Mounting Clip
SL8900-57	Acrylic End Cap

CUSTOMISATION OPTIONS

Trafficable Toughened Polycarbonate Diffuser Available
Compatible with all Superlight linear LED options
Mounting profile can be powdercoated by request
RGB control or dimmable single colour control options
Interior & Exterior IP rated options
Optional Toughened Polycarbonate Lens

All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.