

SUPERLIGHT CITY FACADE LINEAR LED FITTING SL9632

Superlight City-Facade is a slimline linear LED luminaire with high quality LED components City-Facade is IP66 rated and available in several lengths and configurations. Excellent for facade lighting, wall washing, exterior or interior projects and multiple fittings can create continuous linear lighting installations.

SPECIFICATIONS

Series Model Number:	SL9632
Input Voltage:	24VDC
Power Consumption:	6W / 8W/ 12W / 18W / 24W
Nominal Fixture Lengths:	300mm / 500mm / 600mm / 1000mm / 1200mm
Profile Dimensions:	26x21mm
Included Accessory:	Adjustable Brackets
Fixture Material:	6063 High Density Anodised Aluminium
LED Classification:	Nichia SMD2835/SMD5050
Typical Light Source Efficacy:	135lm/W
Light Source CRI:	>90
Beam Angle Options:	15° / 25° / 50° / 10x40°
Recommended Ambient Temp:	-20 ~ +55 °C
IP Protection Rating:	IP66



PHOTOMETRIC INFORMATION

SL9632***-15	CCT: 6000K CRI: >90
SL9632***-17	CCT: 4000K CRI: >90
SL9632***-21	CCT: 3000K CRI: >90
SL9632***-27	CCT: 2700K CRI: >90



Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

Wall-washing, Grazing projects, Building facade lighting, landscape lighting, architectural highlighting, commercial projects, hotels & hospitality projects, residential applications, signage and feature lighting, theatres and venues.

CONTROL & DIMMING COMPATIBILITY

Superlight City Facade luminaires are dimmable via PWM control and can be controlled via any Superlight constant voltage PWM dimming interface, Typical options include Superlight 1-10V Analogue, DALI, or DMX512 version is controllable with any Superlight 12/24VDC Colour Controller

ORDERING INFORMATION

SL9632L300	City Facade Linear LED Luminaire IP66 24VDC 300mm
SL9632L500	City Facade Linear LED Luminaire IP66 24VDC 500mm
SL9632L600	City Facade Linear LED Luminaire IP66 24VDC 600mm
SL9632L1000	City Facade Linear LED Luminaire IP66 24VDC 1000mm
SL9632L1200	City Facade Linear LED Luminaire IP66 24VDC 1200mm
SL9632AGL	Asymmetrical Glare Louvre for SL9632

LED Configuration	Single colour inc 2700K / 3000K / 4000K / 5000K
DALI Control	DALI Dimmable via SL5051 / 5052 DALI Control Interface

CUSTOMISATION OPTIONS

Colour can be refinished by special request

Dimmable via DALI, 1-10V, DMX Analogue

Custom options may be subject to minimum order quantities



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

