

## SUPERLIGHT CITY FACADE LINEAR LED FITTING SL9635

Superlight City-Facade is a slimline linear LED luminaire with strong light output and City-Facade is IP66 rated and available in several lengths and configurations. Excellent for facade lighting, wall washing, exterior or interior projects and multiple fittings can be used to create continuous linear lighting installations.

### SPECIFICATIONS

Series Model Number:	SL9635
Input Voltage:	24VDC
Power Consumption:	12W / 24W / 36W
Nominal Fixture Lengths:	500mm / 1000mm
Profile Dimensions:	33x27.5mm
Included Accessory:	Adjustable Brackets
Fixture Material:	6063 High Density Anodised Aluminium
LED Classification:	Nichia SMD2835/SMD5050
Typical Light Source Efficacy:	135lm/W
Light Source CRI:	>90
Beam Angle Options:	30° / 50° / 35v25°
Recommended Ambient Temp:	-20 ~ +55°C
IP Protection Rating:	IP66



### PHOTOMETRIC INFORMATION

SL9635***-15	CCT: 6000K CRI: >90
SL9635***-17	CCT: 4000K CRI: >90
SL9635***-21	CCT: 3000K CRI: >90
SL9635***-35	RGB



Detailed photometric report and IES files available by request

### TYPICAL APPLICATIONS

Wall-washing, Grazing projects, Building facade lighting, landscape lighting, architectural highlighting, commercial projects, hotels & hospitality projects, residential applications, signage and feature lighting, theatres and venues.

### CONTROL & DIMMING COMPATIBILITY

Superlight City Facade luminaires are dimmable via PWM control and can be controlled via any Superlight constant voltage PWM dimming interface, Typical options include Superlight 1-10V Analogue, DALI, or DMX512 RGB/RGBW version is controllable with any Superlight 12/24VDC Colour Controller

### ORDERING INFORMATION

SL9635L500	City Facade Linear LED Luminaire IP66 24VDC 500mm
SL9635L1000	City Facade Linear LED Luminaire IP66 24VDC 1000mm
SL9635GL500	Glare Louvre for 500mm Luminaire
SL9635GL1000	Glare Louvre for 1000mm Luminaire
SL9635AGL500	Asymmetrical Glare Louvre for 500mm Luminaire
SL9635AGL10000	Asymmetrical Glare Louvre for 10000 mm Luminaire

LED Configuration	Single colour inc 2700K / 3000K / 4000K / 5000K
Optional RGB/W	RGB / RGBW DMX512 Version with Built in DMX Decoder

### CUSTOMISATION OPTIONS

Colour can be refinished by special request

RGBW configuration can be with on-board DMX512

Custom options may be subject to minimum order quantities



All product specifications are subject to change without notice. Superlight accepts no liabilities as a result of errors, updates or omissions. Please re-confirm all product details prior to ordering.

