

SL9701 MXV-2 ARCHITECTURAL LED FLOODLIGHT

Superlight MXV-2 LED Floodlights are high-end architecturally designed fittings that provide excellent light output and maximum efficiency. The fittings have integral LED driver and operate on standard mains voltage. They are suitable for general purpose floodlighting and architectural lighting applications.

SPECIFICATIONS

Input Voltage:	85-265VAC
Max Power Consumption:	10W
LED Quantity:	1
LED Classification:	MX LED V.2
Viewing Angle:	120°
Dimensions:	180x135x57mm
IP Rating:	IP65
Typical Efficiency:	>90%
Power Factor:	0.95
Colour Rendering Index CRI:	>80
Recommended Operating Temp:	-5°C ~ +55°C

PHOTOMETRIC INFORMATION

SL9701-15 CCT: 6500K CRI: >85

SL9701-21 CCT: 3200K CRI: >80

Detailed photometric report and IES files available by request

TYPICAL APPLICATIONS

General area floodlighting, Security lighting, Car parks and industrial lighting, Architectural lighting and building facades.

CONTROL & DIMMING COMPATIBILITY

This product is available in dimmable configurations including Phase Dim, DALI, 1-10V, DMX512. Please contact us for options and availability.

ORDERING INFORMATION

SL9701-15	MXV-2 LED Floodlight 10W 6500K COOL WHITE
SL9701-21	MXV-2 LED Floodlight 10W 3200K WARM WHITE

CUSTOMISATION OPTIONS

Fixture colour can be refinished

Customisation options are subject to availability and minimum order quantities

